

AIS PILOT PLUG

NPP100



NPP100 AIS Pilot Plug is an IMO Standard AIS Pilot Plug used for AIS.

- Interface: RS422
- Size: 95 (H) × 78 (W) × 50 (D) mm
- Weight: 0.1 kg
- Operating Temperature: -20°C ~ +55°C
- IP Grade: IP22

AIS PILOT PLUG CABLE

NPP100C



NPP100C AIS Pilot Plug Cable provides a simple and easy way to connect AIS Pilot Plug to your computer, laptop, or pocket PC, work with Marine Navigation Software to show your own ship and the surrounding ship's information.

- IMO Standard AIS Pilot Plug interfaces for mariners.
- Standard USB 2.0 (1.0 compliant).
- Cable length: 1.5 m.
- High-quality shield high speed cable.
- IP Grade: IP22

TEST KIT FOR AIS PILOT PLUG

NPP100T



◆ HOW TO USE

- A good self-test tool for crews before the pilot on board.
- Can be used as a tool to check the plug when needed.
- Can be connected to the plug permanently for real-time monitoring.

◆ WHAT TO CHECK

- Monitor or check the pilot plug.
- Check AIS static data on the plug.
- Check AIS dynamic data on the plug.
- Check AIS target list on the plug.

◆ HOW TO CONNECT

